

HF Reefer 1-2 Interlock Splitter Box

HF Splitter Box allows you to connect 2 reefer units in the same receptacle safely, quickly and easily and without risk of failure or damage to either equipment or personnel.

An interlock function ensures safety for personnel as well as the reefer unit. By allowing plug-in only when the power is off and locking the plug when the power is on, the splitter box provides extra safety.

Including 4m HF Container Flex III 4G4 yellow power cable.

Standards:

Enclosure protection type IP 67 and IK 10, according to EN62262.

Benefits:

- Small size, light weight
- Quick, safe and simple operation
- Watertight
- Designed for the reefer container business
- Suitable for the environment on the vessel
- One MCB per receptacle



Parts description	
Enclosure:	260x360x168mm (WxHxD)
Colour:	RAL7032
Handle:	Foldable carrying handle
MCB:	2 x MCB 3p 20A type D 10kA
Window:	Hinged window (6modul)
Receptacle:	2 x CEE power receptacle 3p+E, 32A, 3H 440 V
Interlock:	Mechanical Interlock
Power plug:	CEE power plug 3p+E, 32A, 3H 440 V
Power cable:	4m H07 RN-F 4G4mm ² power cable
Safety class:	IP 67 – IK10
Internal wiring:	10AWG, colour coded

Hans Følsgaard A/S reserves the right to change and modify the features and specifications of HF Reefer Splitter Box without prior notification